




## 鋼索 WIRE




7X19



7X7



1X7



6X24

### 不鏽鋼鋼索 SUS304

DIA MM	SPEC	荷重 KG	淨重 KG/M	牌價 NTD/M	牌價 NTD/KG
0.6		-	-		
0.8		-	-		
1.0		11.8	-		
1.5	7X7	-	0.009		
2.0		47.5	0.016		
2.5		74.5	0.025		
3.2		124.5	0.041		
4.0		190	0.064		
2.0	7X19	47.5	0.016		
2.5		74.5	0.025		
3.2		122	0.041		
4.0		190	0.064		
5.0		297	0.1		
6.0		380	0.144		
8.0		675	0.256		
9.0		855	0.324		
10		1057	0.4		
12		1522	0.576		
16	3220	1.024			

### 鋼索

DIA MM	SPEC	荷重 KG	淨重 KG/M	牌價 NTD/M	牌價 NTD/KG
4.0 鋼芯	表面 股 X 芯	162	0.058		
5.0 鋼芯	鍍鋅 7x19	254	0.064		
6.0 鋼芯		360	0.120		
8.0 麻芯		644	0.212		
9.0 麻芯	黑鐵 6x24	814	0.269		
10 麻芯		1006	0.332		
12 麻芯		1448	0.478		
16 麻芯		2000	0.850		
20 麻芯		4020	1.330		

### 鋁合金壓頭

MM	3.0	4.0	5.0	6.0	8.0	9.0	10	12	16	20
牌價	3.0	5.0	7.0	9.0	15	20	26	31	59	110